



CWST

Heat-shrinkable wraparound repair sleeve

Features

- CWST repair sleeves are based on the RayFort technology of heat shrinkable composite materials. The CWST wraparound sleeves are suitable for repair of all types of unpressurised cable: aerial, buried or ducted, non filled or jelly filled with polyethylene or metal jackets.
- An integrated moisture barrier completely reconstitutes the cable sheath construction.
- The hotmelt adhesive coated on the sleeve ensures a permanent, reliable, watertight seal.
- The excellent split resistance of the composite structure offers superior resistance to mechanical abuse during and after the installation.
- The installation indicators: heat sensitive paint, adhesive flow and the white line facilitate correct installations.
- Unlimited shelf life.
- Extended size range can accommodate cables with diameters ranging from 8 to 200 mm.

CWST

Heat-shrinkable wraparound repair sleeve



This cable jacket, damaged by an excavator, is quickly repaired.



The CWST sleeve is simply wrapped around the damaged cable area and shrunk with a standard joiner's torch.

Ordering Information (dimensions in mm)

Description	Max. cable dia.	Min. cable dia.	Lengths supplied
CWST 43/8	43	8	1500, 1000, 750, 500, 250
CWST 55/12	55	12	1500, 1000, 750, 500, 250
CWST 75/15	75	15	1500, 1000, 750, 500, 250
CWST 100/25	100	25	1500, 1000, 750, 500, 250
CWST 137/34	137	34	1500, 1000, 750, 500, 250
CWST 125/30	125	30	1500, 1000, 750, 500, 250
CWST 164/42	164	42	1500, 1000, 750, 500, 250
CWST 200/50	200	50	1500, 1000, 750, 500, 250



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-322452-EU (01/16) [Reviewed from TC 228/DS/6 04/07]